

## TCD-20G4



### 1/3" VANDAL, MONO DOME CAMERA WITH VARIFOCAL, AUTO-IRIS LENS

- >>>> 1/3" Mono Sony CCD
- >>>> Full internal pivot bracket -enables wall or ceiling mounting
- >>>> Low light capabilities down to 0.2 Lux @ F1.2
- >>>> Varifocal, auto iris 4-9.0mm lens
- >>>> Vandal resistant designed housing with tamper proof dome cover
- >>>> Water resistant (IP66)



Model Number	TCD-20G4
Image Sensor Device	1/3" Mono Sony CCD
Total pixels	PAL : 795 x 596
H. Sync. Frequency	PAL/ CCIR : 15.625 KHz
V. Sync. Frequency	PAL/ CCIR : 50Hz
Synchronisation System	DC : Internal/ AC : Line Lock (option)
Horizontal Resolution	> 580 TVL
Back Light Compensation (BLC)	Auto
Electronic Shutter (ES)	Switch On/ Off PAL : 1/50 ~ 1/100,000 sec
Auto Gain Control (GC)	Auto
Gamma Correction	0.45
S/N Ratio	More than 48dB (AGC off)
Video Output	1.0Vpp, 75 Ohms
Minimum Illumination	0.2 Lux @ F1.2
White Balance	Auto
Lens Standard	Varifocal, auto-iris 4.0-9mm lens
Operating Temperature	-10°C ~ +50°C
Storage Temperature	-30°C ~ +60 °C
Power Requirement	DC 12V (+/- 10%) or AC24V (+/- 10%)
Power Consumption	180mA (DC)
Dimension	108(w)x 75(h) mm
Weight	640g